

FortiGate® 5000 Series

Scalable Data Center and Carrier Grade Security Systems

Next Generation Firewall
Segmentation
IPS
Mobile Security

The FortiGate 5000 series delivers high-performance threat protection and SSL inspection for large enterprises and service providers, with the flexibility to be deployed at the enterprise/cloud edge, in the data center core or internal segments. The multiple high-speed interfaces, high port density, superior security efficacy, and high throughput of the 5000 series keep your network connected and secure.



Security

- Identifies thousands of applications inside network traffic for deep inspection and granular policy enforcement
- Protects against malware, exploits, and malicious websites in both encrypted and non-encrypted traffic
- Prevents and detects against known and unknown attacks using continuous threat intelligence from AI-powered FortiGuard Labs security services

Performance

- Delivers industry's best threat protection performance and ultra-low latency using purpose-built security processor (SPU) technology
- Provides industry-leading performance and protection for SSL encrypted traffic

Certification

- Independently tested and validated best security effectiveness and performance
- Received unparalleled third-party certifications from NSS Labs

Networking

- Delivers advanced networking capabilities that seamlessly integrate with advanced layer 7 security and virtual domains (VDMs) to offer extensive deployment flexibility, multi-tenancy, and effective utilization of resources
- Delivers high-density, flexible combination of various high-speed interfaces to enable best TCO for customers for data center and WAN deployments

Management

- Includes a management console that is effective, simple to use, and provides comprehensive network automation & visibility.
- Provides Zero Touch Integration with Security Fabric's Single Pane of Glass Management
- Predefined compliance checklist analyzes the deployment and highlights the best practices to improve overall security posture

Security Fabric

- Enables Fortinet and Fabric-ready partners' products to provide broader visibility, integrated end-to-end detection, threat intelligence sharing, and automated remediation

Model	FG-5001D*	FG-5001E*	Fully-Populated FG-5144C**
Firewall	80 Gbps	80 Gbps	1.12 Tbps
Concurrent Sessions (TCP)	23 Million	40 Million	560 Million
New Sessions/Second (TCP)	565,000	640,000	8,960,000
IPS	13 Gbps	18 Gbps	252 Gbps
NGFW	10 Gbps	15 Gbps	210 Gbps
Threat Protection	7.7 Gbps	13.5 Gbps	189 Gbps
Network Interfaces	Multiple 40 GE QSFP+ and 10 GE SFP+ slots	Multiple 40 GE QSFP+ and 10 GE SFP+ slots	Multiple 40 GE QSFP+ and 10 GE SFP+ slots

Refer to specification table for details. * Each Security Blade. ** With FG-5001E security blades

Deployment



Next Generation Firewall (NGFW)

- Reduce complexity by combining threat protection security capabilities into a single high-performance network security appliance
- Identify and stop threats with powerful intrusion prevention beyond port and protocol that examines the actual applications in your network traffic
- Delivers industry's highest SSL inspection performance using industry-mandated ciphers while maximizing ROI
- Proactively blocks newly discovered sophisticated attacks in real-time with advanced threat protection



Segmentation

- Intent-based Segmentation builds robust security framework while proactively reducing risk, cost and complexity
- Integrates with Security Fabric seamlessly to allow third-party solutions and continuous trust assessment thereby preventing sophisticated attacks
- Protects critical business applications and helps implement any compliance without network redesigns




IPS

- Highly cost-effective mitigation of unpatched vulnerability for hard-to-patch systems such as IOT, ICS, and Scada
- Protect sensitive data to achieve various regulatory compliance such as PCI, HIPPA, PII, GDPR
- Multiple inspection engines, threat intelligence feeds and advanced threat protection options to defend against unknown threats in real-time
- Best of breed intrusion prevention with high-performance SSL inspection




Mobile Security for 4G, 5G and IOT

- SGi LAN security powered by multiple SPUs to provide high-performance CGNAT and accelerate IPv4 and IPv6 traffic
- RAN Access Security with highly scalable and the best performing IPsec aggregation and control security gateway (SecGW)
- User plane security enabled by full Threat Protection and visibility into GTP-U inspection
- Signaling security to inspect various protocols such as SCTP, Diameter, GTP-C, SIP, and provide protection against attacks
- High-speed interfaces to enable deployment flexibility



FortiGate 5000 Series deployment in large campus networks (NGFW, Intent-based Segmentation)




FortiGate 5000 Series deployment in data center (IPS/NGFW, Intent-based Segmentation)

Architecture

Flexible and Scalable

- Chassis and blades systems that can be configured for various resiliency and network requirements
- Security blades can be added as demand grows
- Ease of maintenance and minimum disruption with hot swappable components



Chassis

The chassis enables the flexible system to scale effortlessly by allowing blades to be hot-swapped according to desired requirements. The system can also be configured for various resilience designs within the chassis as well as between chassis. The rack-mount ATCA chassis provides centralized and redundant power supplies to its blades and may be powered by either DC or AC with an additional power interface. It facilitates backplane communications between the blades which may be used for HA heartbeat and other control and data communications.

The FortiGate 5144C and FortiGate 5060 may house shelf managers that control chassis power allocation, monitor chassis operating parameters, monitor and control chassis cooling, and can signal alerts via the alarm module if the chassis encounters problems.

Security Blades

High performance, Security Processing Unit (SPU) powered security blades run on FortiOS or FortiCarrier which apply access policies and security profiles on the traffic they receive from the networking blades via backplane or front panel interfaces. These blades may operate in NAT/route and/or transparent mode. They also support VDOMs (virtual domains) within the cluster.

Networking Blades


Up to two networking blades may be installed on a FortiGate 5144C and FortiGate 5060 in designated slots. These blades connect the system to the network while connected to the multiple security blades via the chassis backplane. The networking blade clusters the security blades with traffic distribution.

Networking blades can assign security blades into service groups which are isolated clusters coexisting in a single chassis. Two networking blades may either operate as active-passive HA or separately with its clusters.

Chassis

FortiGate 5144C

Next Generation 14U 19-inch rack mount ATCA chassis with 40 Gbps Backplane and capable of Dual-Dual-Star topology. It can install up to 14 FortiGate 5000 series blades.



	FG-5144C
Hardware Specifications	
Available Slots	14
High Availability Backplane Fabric	Built-in
40 Gbps Backplane Support	Yes
Shelf Manager (Default / Maximum)	1 / 2
Dual Networking Blade Support	Yes
Dimensions	
Height x Width x Length (inches)	24.44 x 19.06 x 21.63
Height x Width x Length (cm)	62.1 x 48.4 x 55.0
Weight	108 lbs (50 kg)
Maximum Capacity**	
Firewall Throughput	1.12 Tbps

	FG-5144C
Power and Environment	
Power Required	DC/AC ¹
Chassis Only Power Consumption (Maximum) ***	960 W
Heat Dissipation (Maximum) ***	3,276 BTU/h
Operating Temperature	32–104°F (0–40°C)
Storage Temperature	-13–158°F (-35–70°C)
Humidity	5–90% non-condensing
Compliance	
Certifications	FCC Part 15 Class A, C-Tick, VCCI, CE, BSMI, UL/cUL
NEBS Certified	Yes

¹ Optional FortiGate 5053B Power Supply Shelf used to provide AC power to the FortiGate

** Based on fully-populated FortiGate 5001D

*** Please refer to respective Chassis Guide for computation of total power requirement.


AdvancedTCA™-compliant Chassis

- Based on industry-conforming standards assuring carrier-grade performance, reliability, 99.999% availability and serviceability
- Redundant fans, power modules, self managers and alarm modules options
- Highly scalable with minimum service disruptions as hot swapped blades may be added to increase capacity with ease
- Comprehensive management and monitoring facilities via shelf managers and alarm modules

Security Blades



FortiGate 5001D

Security blade powered by CP8 and NP6 for superior firewall and UTM performance.



FortiGate 5001E/5001E1

Latest purpose-built FortiGate security blade with carrier-class capacity and protection.





	FG-5001D	FG-5001E/5001E1
Interfaces and Storage		
40 GE QSFP+ Ports	2	2
10 GE SFP+ Ports	2	2
GE RJ45 Ports	2	2
RJ45 Console Port	1	1
Included Transceivers	2x 10 GE SFP+ SR	2x 10 GE SFP+ SR
Local Storage	1x 200 GB SSD	1x 480 GB SSD (5001E1)
System Performance		
Firewall Throughput (1518 / 512 / 64 byte UDP packets)	80 / 80 / 45 Gbps	80 / 80 / 50 Gbps
Firewall Latency (64 byte UDP packets)	3 µs	3 µs
Firewall Throughput (Packets Per Second)	67.5 Mpps	75 Mpps
Concurrent Sessions (TCP)	23 Million	40 Million
New Sessions/Second (TCP)	565,000	640,000
Maximum Firewall Policies	200,000	200,000
IPsec VPN Throughput (512 byte packets)	25 Gbps	45 Gbps
Gateway-to-Gateway IPsec VPN Tunnels	40,000	40,000
Client-to-Gateway IPsec VPN Tunnels	64,000	64,000
SSL-VPN Throughput	6.5 Gbps	9 Gbps
Concurrent SSL-VPN Users (Recommended Maximum)	25,000	25,000
IPS Throughput (HTTP / Enterprise Mix) ¹	18 / 13 Gbps	25 / 18 Gbps
SSL Inspection Throughput ²	6.85 Gbps	15 Gbps
SSL Inspection CPS (IPS, avg. HTTPS) ³	3,611	8,805
SSL Inspection Concurrent Session (IPS, avg. HTTPS) ³	1.7 Million	3.97 Million
Application Control Throughput ³	18 Gbps	36 Gbps
NGFW Throughput ⁴	10 Gbps	15 Gbps
Threat Protection Throughput ⁵	7.7 Gbps	13.5 Gbps
CAPWAP Throughput	15 Gbps	15 Gbps
Virtual Domains (Default / Maximum)	10 / 500	10 / 500
Maximum Number of FortiTokens	20,000	20,000
Maximum Number of Registered FortiClients	20,000	20,000
Maximum Number of FortiAPs (Total / Tunnel)	4,096 / 1,024	4,096 / 1,024
Power and Environment		
Power Consumption (Average / Maximum)	189 / 226 W	250 / 278 W
Heat Dissipation (Average)	774 BTU/h	948.6 BTU/h
Operating Temperature	32–104°F (0–40°C)	23–131°F (-5–55°C)
Storage Temperature	-13–158°F (-25–70°C)	-40–158°F (-40–70°C)
Humidity	10–90% non-condensing	10–90% non-condensing
Compliance		
Certifications	FCC Part 15 Class A, C-Tick, VCCI, CE, UL/cUL, CB, ICSA Labs: Firewall, IPsec, IPS, Antivirus, SSL-VPN	
NEBS Certified	Yes	–

Note: All performance values are "up to" and vary depending on system configuration. IPsec VPN performance is based on 512 byte UDP packets using AES-256+SHA1. 1. IPS performance is measured using 1 Mbyte HTTP and Enterprise Traffic Mix. 2. SSL Inspection is measured with IPS enabled and HTTP traffic, using TLS v1.2 with AES256-SHA. 3. Application Control performance is measured with 64 Kbytes HTTP traffic. 4. NGFW performance is measured with IPS and Application Control enabled, based on Enterprise Traffic Mix. 5. Threat Protection performance is measured with IPS and Application Control and Malware protection enabled, based on Enterprise Traffic Mix. 6. CAPWAP performance is based on 1444 byte UDP packets.

Networking Blades

FortiController 5903C/5913C

High Performance networking blade that provides 10/40-gigabit fabric and 1-gigabit base backplane channel layer-2 switching in a dual star architecture.





	FCTL-5903C	FCTL-5913C
Interfaces		
Fabric Channel Interfaces	4x 40 GE QSFP+	2x 100 GE CFP2
Base Channel Interfaces	2x 10 GE SFP+	2x 10 GE SFP+
Management Interfaces	1x GE RJ45	1x GE RJ45
Included Transceivers	2x 10 GE SFP+ SR	2x 10 GE SFP+ SR
40 GE Backplane Fabric Support	Yes	Yes
10 GE Backplane Fabric Support	Yes	Yes
GE Backplane Fabric Support	–	–
System Performance		
Maximum Traffic Throughput	120 Gbps	200 Gbps
Maximum Concurrent Sessions	135 Million	135 Million
New Sessions/Second (TCP)	3.2 Million	3.6 Million

	FCTL-5903C	FCTL-5913C
Power and Environment		
Power Consumption (Average / Maximum)	250 / 400 W	280 / 400 W
Heat Dissipation	1360 BTU/h	955 BTU/h
Operating Temperature	32–104°F (0–40°C)	32–104°F (0–40°C)
Storage Temperature	-13–158°F (-35–70°C)	-13–158°F (-35–70°C)
Humidity	20–90% non-condensing	5–90% non-condensing
Compliance		
Certifications	FCC Part 15 Class A, C-Tick, VCCI, CE, UL/cUL, CB	
NEBS Certified	Yes	Yes

AC Power Supplies

FortiGate 5053B and Power Supply Unit 5000B

The FortiGate 5053B is a 1U 19-inch rack mount power supply shelf with PSU-5000B hot swappable power supplies to convert AC power to DC power and to supply power to a FortiGate 5000 series chassis.



	NON-REDUNDANT				REDUNDANT		
	1	2	3	4	1+1	2+1	3+1
5053B with PSU-5000B (185–307V AC High Line Input)	2,725 W	5,450 W	8,175 W	10,900 W	2,725 W	5,450 W	8,175 W
5053B with PSU-5000B (100–184V AC Low Line Input, North America, Mexico, Japan, etc.)	1,200 W	2,400 W	3,600 W	4,800 W	1,200 W	2,400 W	3,600 W

Additional Available Components

Chassis

FG-5060	
Hardware Specifications	
Available Slots	6
High Availability Backplane Fabric	Built-in
40 Gbps Backplane Support	—
Shelf Manager (Default / Maximum)	1 / 2
Dual Networking Blade Support	Yes
Dimensions	
Height x Width x Length (inches)	8.86 x 17.64 x 18.82
Height x Width x Length (cm)	22 x 44.8 x 47.8
Weight	38 (17.3 kg)
Maximum Capacity**	
Firewall Throughput	480 Gbps

FG-5060	
Power and Environment	
Power Required	DC/AC ¹
Chassis-Only Power Consumption (Maximum) ***	350 W
Heat Dissipation (Maximum) ***	1194 BTU/h
Operating Temperature	41–104°F (5–40°C)
Storage Temperature	23–131°F (-5–55°C)
Humidity	5–85% non-condensing
Compliance	
Certifications	FCC Part 15 Class A, C-Tick, VCCI, CE, BSMI, UL/cUL
NEBS Certified	—

¹ Optional FortiGate 5053B Power Supply Shelf used to provide AC power to the FortiGate

** Based on fully populated FortiGate 5001D

*** Please refer to respective Chassis Guide for computation of total power requirement.

Security Blades

FG-5001C	
Interfaces and Storage	
40 GE QSFP+ Ports	—
10 GE SFP+ Ports	2
GE RJ45 Ports	2
RJ45 Console Port	1
Included Transceivers	2x 10 GE SFP+ SR
Local Storage	128 GB
System Performance	
Firewall Throughput (1518 / 512 / 64 byte UDP packets)	40 / 40 / 40 Gbps
Firewall Latency (64 byte UDP packets)	4 μs
Firewall Throughput (Packets Per Second)	60 Mpps
Concurrent Sessions (TCP)	29.5 Million
New Sessions/Second (TCP)	210,000
Maximum Firewall Policies	200,000
IPsec VPN Throughput (512 byte packets)	17 Gbps
Gateway-to-Gateway IPsec VPN Tunnels	40,000
Client-to-Gateway IPsec VPN Tunnels	64,000
SSL-VPN Throughput	3.6 Gbps
Concurrent SSL-VPN Users (Recommended Maximum)	20,000
IPS Throughput	12 Gbps
Virtual Domains (Default / Maximum)	10 / 500
Maximum Number of FortiTokens	5,000
Maximum Number of Registered FortiClients	20,000
Maximum Number of FortiAPs (Total / Tunnel)	4,096 / 1,024

FG-5001C	
Power and Environment	
Power Consumption (Average / Maximum)	187 / 225 W
Heat Dissipation (Average)	768 BTU/h
Operating Temperature	32–104°F (0–40°C)
Storage Temperature	-13–158°F (-25–70°C)
Humidity	20–90% non-condensing
Compliance	
Certifications	FCC Part 15 Class A, C-Tick, VCCI, CE, UL/cUL, CB, ICESA Labs: Firewall, IPsec, IPS, Antivirus, SSL-VPN
NEBS Certified	—

* Operating in Standalone Mode

Note: All performance values are "up to" and vary depending on system configuration. IPS performance is measured using 1 Mbyte HTTP files. IPsec VPN performance is based on 512 byte UDP packets using AES-256+SHA1.

Fortinet Security Fabric

Security Fabric


The Security Fabric delivers broad visibility, integrated AI-driven breach prevention, and automated operations, orchestration, and response across all Fortinet and its ecosystem deployments. It allows security to dynamically expand and adapt as more and more workloads and data are added. Security seamlessly follows and protects data, users, and applications as they move between IoT, devices, and cloud environments throughout the network. All this is tied together under a single pane of glass management to deliver leading security capabilities across your entire environment while also significantly reducing complexity.

FortiGates are the foundation of Security Fabric, expanding security via visibility and control by tightly integrating with other Fortinet security products and Fabric-Ready Partner solutions.



FortiOS

Control all security and networking capabilities across the entire FortiGate platform with one intuitive operating system. Reduce complexity, costs, and response time with a truly consolidated next-generation security platform.



Services



FortiGuard Labs offers real-time intelligence on the threat landscape, delivering comprehensive security updates across the full range of Fortinet’s solutions. Comprised of security threat researchers, engineers, and forensic specialists, the team collaborates with the world’s leading threat monitoring organizations and other network and security vendors, as well as law enforcement agencies.



Our FortiCare customer support team provides global technical support for all Fortinet products. With support staff in the Americas, Europe, Middle East, and Asia, FortiCare offers services to meet the needs of enterprises of all sizes.

For more information, please refer to forti.net/fortiguard and forti.net/forticare

Order Information

PRODUCT	SKU	DESCRIPTION
Chassis		
FortiGate 5144C Chassis	FG-5144C-DC	14U 14-slot chassis with 40G Dual Star fabric backplane, 4 PEMs, 4 fan units, 2 shelf FRU data modules, 1 shelf manager, front and RTM air baffles, and 4 pairs DC cables for connecting to FG-5053B power shelves
FortiGate 5144C-DC Chassis	FG-5144C-DC-NEBS	14U 14-slot chassis with 40G Dual Star fabric backplane, 4 PEMs, 4 fan units, 2 shelf FRU data modules, 1 shelf manager, front and RTM air baffles, and 4 pairs DC cables for connecting to FG-5053B power shelves, NEBS certified
FortiGate 5144C Shelf Manager	FG-5144C-SM	5144C shelf manager with ShMM-700R mezzanine card and radial IPMB bus
FortiGate 5144C Fan Tray	FG-5144C-FAN-F	FG-5144C fan tray front
FortiGate 5144C Fan Tray	FG-5144C-FAN-R	FG-5144C fan tray rear
FortiGate 5144C Shelf FRU Data Module	FG-5144C-SFRU	FG-5144C shelf FRU data module
FortiGate 5144C Power Entry Module	FG-5144C-PEM	FG-5144C PEM, power entry module
FortiGate 5144C Air Filter	FG-5144C-AF	FG-5144C air filter
FortiGate 5144C Blank Panel	FG-5144C-ABF	5000 front slot blank panel with air baffle (aluminum/plastic)
FortiGate 5144C Blank Panel	FG-5144C-ABR	5000 RTM slot blank panel with air baffle (aluminum/plastic)
FortiGate 5060 Chassis	FG-5060-DC	5U 6-slot chassis with Dual Star fabric backplane, 2 PEMs, 2 fan units, 2 shelf FRU data modules, 1 shelf manager, front and RTM air baffles, and 2 pairs DC cables for connecting to FG-5053B power shelves
FortiGate 5060 Fan Tray	FG-5060FA	Fan tray for FG-5060 chassis
FortiGate 5060 Shelf Manager	FG-5060SM	Shelf manager for FG-5060 chassis
FortiGate 5060 Shelf Alarm Panel	FG-5060SAP	Shelf alarm panel for FG-5060 chassis
FortiGate 5053B Power Converter Tray	FG-5053B	AC power converter shelf for high capacity 5000 chassis, supports up to 4 PSU-5000B power supply units, unpopulated
FortiGate 5000 Series Power Supply Unit	PSU-5000B	Power supply unit for FG-5000 series, AC power supply unit, 1,200 Watts maximum, requires FortiGate 5053B shelf
Security Blades		
FortiGate 5001E	FG-5001E	Security blade with 2x 40 GE QSFP+ ports, 2x 10 GE SFP+ ports, 2x GE RJ45 management ports, FortiASIC NP6 and CP9 hardware accelerated
FortiGate 5001E1	FG-5001E1	Security blade with 2x 40 GE QSFP+ ports, 2x 10 GE SFP+ ports, 2x GE RJ45 management ports, FortiASIC NP6 and CP9 hardware accelerated, 480 GB SSD onboard storage
FortiGate 5001D	FG-5001D	Security blade with 2x 40 GE QSFP+ ports, 2x 10 GE SFP+/GE SFP ports, 2x GE RJ45 management ports, 200 GB SSD onboard storage
FortiGate 5001C	FG-5001C	Security blade with 2x 10 GE SFP+ ports, 2x GE RJ45 management ports, 128 GB SSD onboard storage
Networking Blades		
FortiController 5903C	FCTRL-5903C	Networking blade with 4x 40 GE SFP+ fabric slots, 2x 10 GE SFP+ base slots, 1x GE RJ45 management port
FortiController 5913C	FCTRL-5913C	Networking blade with 2x 100 GE CFP2 fabric slots, 2x 10 GE SFP+ base slots, includes 2 SR SFP+
Optional Accessories		
1 GE SFP LX Transceiver Module	FG-TRAN-LX	1 GE SFP LX transceiver module for all systems with SFP and SFP/SFP+ slots
1 GE SFP RJ45 Transceiver Module	FG-TRAN-GC	1 GE SFP RJ45 transceiver module for all systems with SFP and SFP/SFP+ slots
1 GE SFP SX Transceiver Module	FG-TRAN-SX	1 GE SFP SX transceiver module for all systems with SFP and SFP/SFP+ slots
10 GE SFP+ Transceiver Module, Short Range	FG-TRAN-SFP+SR	10 GE SFP+ transceiver module, short range for all systems with SFP+ and SFP/SFP+ slots
10 GE XFP Transceiver Module, Short Range	FG-TRAN-XFPSR	10 GE XFP transceiver module, short range for all systems with XFP slots
10 GE SFP+ Transceiver Module, Long Range	FG-TRAN-SFP+LR	10 GE SFP+ transceiver module, long range for all systems with SFP+ and SFP/SFP+ slots
10 GE XFP Transceiver Module, Long Range	FG-TRAN-XFPLR	10 GE XFP transceiver module, long range for all systems with XFP slots
40 GE QSFP+ Transceivers, Short Range	FG-TRAN-QSFP+SR	40 GE QSFP+ transceivers, short range for all systems with QSFP+ slots
100 GE CFP2 Transceivers, Long Range	FG-TRAN-CFP2-LR4	100 GE CFP2 transceivers, long range, over single mode fiber, for all systems with CFP2 slots
100 GE CFP2 Transceivers, Short Range	FG-TRAN-CFP2-SR10	100 GE CFP2 transceivers, 10 channel parallel fiber, short range for all systems with CFP2 slots
10 GE SFP+ Active Direct Attach Cable	SP-CABLE-ADASFP+	10 GE SFP+ active direct attach cable, 10m / 32.8 ft for all systems with SFP+ and SFP/SFP+ slots

More Features with FortiCarrier Software License

- SIP/IMS signaling firewall protects internal infrastructure and service against malicious messages and overload while providing NAT services and redundancy, providing VoIP edge scalability and a platform for managed security services
- MMS security — content scanning and protection (keyword blocking, antivirus, file-type blocking, antispyware detection) with per-user services provide enhanced end-user security for increased uptime and higher customer satisfaction
- GTP firewall delivers protocol anomaly detection and prevention with multiple filter options for end-to-end security

Bundles



FortiGuard Bundle

FortiGuard Labs delivers a number of security intelligence services to augment the FortiGate firewall platform. You can easily optimize the protection capabilities of your FortiGate with one of these FortiGuard Bundles.

Bundles	360 Protection	Enterprise Protection	UTM	Threat Protection
FortiCare	ASE ¹	24x7	24x7	24x7
FortiGuard App Control Service	•	•	•	•
FortiGuard IPS Service	•	•	•	•
FortiGuard Advanced Malware Protection (AMP) — Antivirus, Mobile Malware, Botnet, CDR, Virus Outbreak Protection and FortiSandbox Cloud Service	•	•	•	•
FortiGuard Web Filtering Service	•	•	•	
FortiGuard Antispam Service	•	•	•	
FortiGuard Security Rating Service	•	•		
FortiGuard Industrial Service	•	•		
FortiCASB SaaS-only Service	•	•		
FortiConverter Service	•			
SD-WAN Cloud Assisted Monitoring ²	•			
SD-WAN Overlay Controller VPN Service ²	•			
FortiAnalyzer Cloud ²	•			
FortiManager Cloud ²	•			

1. 24x7 plus Advanced Services Ticket Handling 2. Available when running FortiOS 6.2